



Technical specifications	quadro 599 TST	quadro 799 TST	quadro 899 TST
Ord. no.	40.431	40.432	40.434
Operating pressure, continuously adjustable	30-150 bar / 3-15 MPa	30-180 bar / 3-18 MPa	30-150 bar / 3-15 MPa
Max. admissible overpressure	165 bar / 16.5 MPa	200 bar / 20 MPa	170 bar / 17 MPa
Water output	10 l/min (600 l/h)	13 l/min (780 l/h)	15 l/min (900 l/h)
Volume water tank	10 l	10 l	10 l
Motor speed	1.400 rpm	1.400 rpm	1.400 rpm
Connected load	230 V, 14 A, 50 Hz	400 V, 8.5 A, 50 Hz	400 V, 8.5 A, 50 Hz
Power intake / Power output	3.3 kW / 2.4 kW	5.5 kW / 4.0 kW	5.5 kW / 4.0 kW
Weight	62 kg	62 kg	62 kg
Features & Equipment	Ord. no.	Ord. no.	Ord. no.
Steel braided high-pressure hose, with hose drum	43.416 1 (20 m, NW 6)	43.416 1 (20 m, NW 6)	44.879 (15 m, NW 8)
Trigger gun with safety catch M2000	12.480	12.480	12.480
Dirtkiller lance with stainless steel pipe	46.150	46.150 1	46.150 2
Stainless steel lance with flat jet nozzle	12.392 2-M20035	12.392 2-M20045	12.392 2-D2506