



Technical specifications	therm C 11/130	therm C 13/180	therm C 15/150
Ord. no. without hose drum	41,442	41,441	41,440
Ord. no. with hose drum	41,442 1	41,441 1	41,440 1
Operating pressure, continuously adjustable	30-130 bar / 3-13 MPa	30-180 bar / 3-18 MPa	30-150 bar / 3-15 MPa
Max. admissible overpressure	145 bar / 14.5 MPa	200 bar / 20 MPa	170 bar / 17 MPa
Water output	11 l/min (660 l/h)	13 l/min (780 l/h)	15 l/min (900 l/h)
Hot water output temperature (water supply 12 °C) continuously adjustable	12 - 80 °C	12 - 80 °C	12 - 80 °C
Steam level	max. 140 °C	max. 150 °C	max. 150 °C
Heating output	55 kW	60 kW	65 kW
Fuel tank capacity monitoring	25 l	25 l	25 l
Motor speed	1,400 rpm	1,400 rpm	1,400 rpm
Connected load	230 V, 15.0 A, 50 Hz	400 V, 8.7 A, 50 Hz	400 V, 8.7 A, 50 Hz
Power intake / Power output	3.4 kW / 2.3 kW	4.8 kW / 4.0 kW	4.8 kW / 4.0 kW
Weight with hose drum	179 kg	179 kg	179 kg
Features & Equipment	Ord. no.	Ord. no.	Ord. no.
Steel braided high-pressure hose, NW 8	10 m (44,878)	10 m (44,878)	10 m (44,878)
Steel braided high-pressure hose, NW 8	15 m (44,879)	15 m (44,879)	15 m (44,879)
One piece trigger gun with safety catch M2000 with lance and flat jet nozzle	(12,486-D25045)	(12,486-D25045)	(12,486-D25055)
Water inlet filter	(13,310)	(13,310)	(13,310)