



| Technical specifications | therm CA 11/130 | therm CA 12/150 | therm CA 15/120 |
|--|-----------------------|-----------------------|-----------------------|
| Ord. no. without hose drum | 41,460 | 41,461 | 41,462 |
| Ord. no. with hose drum | 41,460 1 | 41,461 1 | 41,462 1 |
| Operating pressure, continuously adjustable | 30-130 bar / 3-13 MPa | 30-150 bar / 3-15 MPa | 30-120 bar / 3-12 MPa |
| Max. admissible overpressure | 145 bar / 14.5 MPa | 170 bar / 17 MPa | 135 bar / 13.5 MPa |
| Water output | 11 l/min (660 l/h) | 12 l/min (720 l/h) | 15 l/min (900 l/h) |
| Hot water output temperature (water supply 12 °C) continuously adjustable | 12 - 82 °C | 12 - 80 °C | 12 - 80 °C |
| Steam level | max. 140 °C | max. 140 °C | max. 150 °C |
| Heating output | 55 kW | 58 kW | 65 kW |
| Fuel tank capacity monitoring | 25 l | 25 l | 25 l |
| Motor speed | 1,400 rpm | 1,400 rpm | 1,400 rpm |
| Connected load | 230 V, 15.0 A, 50 Hz | 400 V, 7.2 A, 50 Hz | 400 V, 7.2 A, 50 Hz |
| Power intake / Power output | 3.4 kW / 2.3 kW | 3.8 kW / 3.0 kW | 3.8 kW / 3.0 kW |
| Weight with hose drum | 171 kg | 172 kg | 181 kg |
| Features & Equipment | Ord. no. | Ord. no. | Ord. no. |
| Steel braided high-pressure hose, NW 8, without hose drum | 10 m (44,878) | 10 m (44,878) | 10 m (44,878) |
| Steel braided high-pressure hose, NW 8, with hose drum | 15 m (44,879) | 15 m (44,879) | 15 m (44,879) |
| One piece trigger gun with safety catch M2000 with lance and flat jet nozzle | (12,486-D25045) | (12,486-D25045) | (12,486-D2507) |
| Water inlet filter | (13,310) | (13,310) | (13,310) |