


# HD-Series



► **ACCESSORIES** | page 74-96



### EQUIPMENT

- Quick release plug-in system D12
- Kränzle axial pump
- Total-Stop system
- Stepless pressure regulation
- Direct suction: Suction height HD 9/80 TS: 1.5 m | HD 12/130 TS: 2.5 m
- High-pressure hose with Twist-Stop screw connection



MODEL	HD 9/80 TS	HD 12/130 TS
Ord.no.	600130	600180

### TECHNICAL SPECIFICATIONS

Operating pressure	bar   MPa	30-80   3-8	30-130   3-13
Water output	l/min   l/h	9   540	11   660
Admissible overpressure	bar   MPa	90   9	145   14.5
Motor speed	Rpm	1400	1400
Connection	V   ~   Hz   A	230   1   50   7.5	230   1   50   13.5
Power intake   Power output	kW	1.6   1.0	2.9   2.2
Power supply cable	m	5	5
Plug		Schuko	Schuko
Dimensions L x W x H	mm	470   230   320	500   240   320
Weight	kg	24	31

### EQUIPMENT

High-pressure hose	m   Ord.no.	10 (DN6)   43416	10 (DN6)   43416
Trigger gun with safety catch	Model   Ord.no.	Starlet 4   12525	Starlet 4   12525
Lance with flat jet nozzle	Nozzle   Ord.no.	● 042   12435-M20042	● 042   12435-M20042
Lance with Dirtkiller	Nozzle   Ord.no.	● 042   12438-042	● 042   12438-042

