

LX-RP-Series



CONVENIENT INTEGRATED HOSE REEL
space-saving storage of the high-pressure hose with twist stop screw connection

ACCESSORY STORAGE
neat storage for high pressure gun and lances

STAINLESS STEEL PROTECTIVE COVER
durable and corrosion resistant

IMPACT PROTECTION
reduces accidental damage to the high-pressure pump

STAINLESS STEEL PRESSURE GAUGE
easy reading of the working pressure

RP IN-LINE PUMP
for magnificent cleaning results with maximum water flow

LX-RP 1600 TST | 616080

► **ACCESSORIES** | page 74-96



EQUIPMENT

- Quick release plug-in system D12
- Kränzle in-line RP pump
- Total-stop system with delayed motor cut-off
- Safety shutdown

- Stepless pressure regulation
- High-pressure hose with Twist-Stop screw connection
- Locking brake
- Direct suction: Suction height 2.5 m



VARIANT - NON-MARKING

NOM conversion kit Ord.no. **42283**

For further information on NON-Marking please refer to page 75

MODEL	LX-RP 1000 TST	LX-RP 1200 TST	LX-RP 1400 TST	LX-RP 1600 TST
Ord.no. TST incl. hose drum	616052	616062	616070	616080

TECHNICAL SPECIFICATIONS

Operating pressure	bar MPa	30-200 3-20	30-190 3-19	30-170 3-17	30-150 3-15
Water output	l/min l/h	16.6 1000	20 1200	23.3 1400	26.7 1600
Admissible overpressure	bar MPa	220 22	210 21	190 19	170 17
Motor speed	Rpm	1400	1400	1400	1400
Connection	V ~ Hz A	400 3 50 13.5	400 3 50 14.3	400 3 50 14.3	400 3 50 14.3
Power intake Power output	kW	7.5 5.5	7.5 5.5	8.0 6.3	8.0 6.3
Power supply cable	m	7.5	7.5	7.5	7.5
Plug		NEW CEE 16 A	NEW CEE 16 A	CEE 32 A	CEE 32 A
Dimensions L x W x H	mm	735 580 1020	735 580 1020	735 580 1020	735 580 1020
Weight	kg	94	94	94	94

EQUIPMENT

High-pressure hose	m Ord.no.	20 (DN8) 443812	20 (DN8) 443812	20 (DN8) 443812	20 (DN8) 443812
Trigger gun with safety catch	Model Ord.no.	Starlet 3 12500	Starlet 3 12500	Starlet 3 12500	Starlet 3 12500
Lance with flat-jet nozzle	Nozzle Ord.no.	05 12420-D2505	065 12420-D40065	08 12420-D4008	11 12420-D4011

