

## Profi-Jet-Series



**STAINLESS STEEL CHASSIS**  
durable and corrosion resistant

**CONVENIENT INTEGRATED HOSE REEL (VARIANT)**  
space-saving storage of the high-pressure hose with twist stop screw connection

**ACCESSORY STORAGE**  
neat storage for high pressure gun and lances

**STAINLESS STEEL PRESSURE GAUGE**  
easy reading of the working pressure

**HONDA PETROL ENGINE**  
reliable, service-friendly, L-type reduction version for optimum pairing, and with low oil protection

**AUTOMATIC SPEED REGULATION**  
reduces fuel consumption and noise levels (from model Profi-Jet B 16/220)

Profi-Jet B 16/220 T | 618049

► **ACCESSORIES** | page 74-96



### EQUIPMENT

- Quick release plug-in system D12
- Kränzle axial pump
- Combustion engine Honda
- Stepless pressure regulation
- High-pressure hose with Twist-Stop screw connection
- Direct suction: Suction height 2.5 m



| MODEL                     | Profi-Jet B 13/150 | Profi-Jet B 10/200 | Profi-Jet B 16/220 | Profi-Jet B 20/200 | Profi-Jet B 16/250 |
|---------------------------|--------------------|--------------------|--------------------|--------------------|--------------------|
| Ord.no. without hose drum | 618003             | 618023             | 618045             | 618065             | 618085             |
| Ord.no. incl. hose drum   | 618007             | 618027             | 618049             | 618069             | 618089             |

### TECHNICAL SPECIFICATIONS

|  |             |                  |                  |                  |                  |                  |
|--|-------------|------------------|------------------|------------------|------------------|------------------|
| Operating pressure                     | bar   MPa   | 30-150   3-15    | 30-200   3-20    | 30-220   3-22    | 30-200   3-20    | 30-250   3-25    |
| Water output                           | l/min   l/h | 13   780         | 10   600         | 16   960         | 20   1200        | 16   960         |
| Admissible overpressure                | bar   MPa   | 170   17         | 220   22         | 240   24         | 220   22         | 270   27         |
| Engine                                 |             | Honda GX160 LX   | Honda GX200 LX   | Honda GX340 LX   | Honda GX390 LX   | Honda GX390 LX   |
| Engine power                           | kW   hp     | 3.6   4.9        | 4.3   5.8        | 8   10.9         | 8.7   11.8       | 8.7   11.8       |
| Speed adjustment                       |             | –                | –                | ●                | ●                | ●                |
| Dimensions L x W x H without hose drum | mm          | 770   570   990  | 770   570   990  | 770   570   990  | 770   570   990  | 770   570   990  |
| Dimensions L x W x H incl. hose drum   | mm          | 770   570   1005 | 770   570   1005 | 785   570   1005 | 785   570   1005 | 785   570   1005 |
| Weight without   incl. hose drum       | kg          | 42   50          | 42   50          | 65   73          | 65   73          | 65   73          |

### EQUIPMENT

|   |                  |                    |                    |                    |                    |                      |
|---|------------------|--------------------|--------------------|--------------------|--------------------|----------------------|
| High-pressure hose <b>without</b> hose drum | m   Ord.no.      | 10 (DN8)   44878   | 10 (DN8)   41081   | 10 (DN8)   41081   | 10 (DN8)   41081   | 10 (DN8)   41081     |
| High-pressure hose <b>incl.</b> hose drum   | m   Ord.no.      | 20 (DN8)   41083   | 20 (DN8)   41083   | 20 (DN8)   41083   | 20 (DN8)   41083   | 20 (DN8)   41083     |
| Trigger gun with safety catch               | Model   Ord.no.  | Starlet 3   12500  | Starlet 3   12500  | Starlet 3   12500  | Starlet 3   12500  | Starlet 3   12500    |
| Lance with regulating nozzle                | Nozzle   Ord.no. | ● 05   12431-D2505 | ○ 03   12431-D2503 | ● 05   12431-D2505 | ● 07   12431-D2507 | ● 045   12431-D25045 |
| Lance with Dirtkiller                       | Nozzle   Ord.no. | ● 05   12425-05    | ○ 03   12425-03    | –                  | –                  | –                    |
| Lance with Turbokiller                      | Nozzle   Ord.no. | –                  | –                  | ● 05   12430-05    | ● 07   12430-07    | ● 045   12430-045    |
| Water inlet filter                          | Ord.no.          | 13310              | 13310              | 13310              | 13310              | 13310                |



**Suction hose with suction filter**

**EXPERT TIP**

For sucking in water from external sources  
■ Hose length 3 m

Ord.no. **150383**