



Technical specifications	quadro 11/140 TST	quadro 9/170 TST	quadro 12/150 TST
Ord. no.	40.441 1	40.443 1	40.442 1
Operating pressure, continuously adjustable	30-140 bar / 3-14 MPa	30-170 bar / 3-17 MPa	30-150 bar / 3-15 MPa
Max. admissible overpressure	155 bar / 15.5 MPa	190 bar / 19 MPa	165 bar / 16.5 MPa
Water output	11 l/min (660 l/h)	9 l/min (540 l/h)	12 l/min (720 l/h)
Volume water tank	7 l	7 l	7 l
Motor speed	1,400 rpm	1,400 rpm	1,400 rpm
Connected load	230 V, 14 A, 50 Hz	230 V, 14 A, 50 Hz	400 V, 6.8 A, 50 Hz
Power intake / Power output	3.3 kW / 2.4 kW	3.3 kW / 2.4 kW	3.5 kW / 2.8 kW
Weight	46 kg	46 kg	46 kg
Features & Equipment	Ord. no.	Ord. no.	Ord. no.
Steel braided high-pressure hose, 15 m NW 6, with hose drum	40.170	40.170	40.170
Trigger gun with safety catch M2000	12.480	12.480	12.480
Dirtkiller lance with stainless steel pipe	41.570-045	41.570-03	41.570-045
Stainless steel lance with flat jet nozzle	12.393-M20045	12.393-M2003	12.393-M20045