



Technical specifications	quadro 800 TST	quadro 1000 TST	quadro 1200 TST	quadro 1500 TST
Ord. no. with standard trolley	40.423	40.421	40.422	40.426
Ord. no. with stainless steel trolley	40.423 0	40.421 0	40.422 0	40.426 0
Operating pressure, continuously adjustable	30-250 bar / 3-25 MPa	30-220 bar / 3-22 MPa	30-180 bar / 3-18 MPa	30-140 bar / 3-14 MPa
Max. admissible overpressure	270 bar / 27 MPa	250 bar / 25 MPa	200 bar / 20 MPa	160 bar / 16 MPa
Water output	13.3 l/min (798 l/h)	16 l/min (960 l/h)	19 l/min (1,140 l/h)	25 l/min (1,500 l/h)
Volume water tank	16 l	16 l	16 l	16 l
Motor speed	1,400 rpm	1,400 rpm	1,400 rpm	1,400 rpm
Connected load	400 V, 12 A, 50 Hz	400 V, 12 A, 50 Hz	400 V, 12 A, 50 Hz	400 V, 12 A, 50 Hz
Power intake / Power output	7.5 kW / 5.5 kW	7.5 kW / 5.5 kW	7.5 kW / 5.5 kW	7.5 kW / 5.5 kW
Weight	89 kg	89 kg	89 kg	89 kg
Features & Equipment	Ord. no.	Ord. no.	Ord. no.	Ord. no.
Steel braided high-pressure hose, 20 m NW 8, with hose drum	41.083	41.083	41.083	41.083
Trigger gun with safety catch Starlet	12.320 2	12.320 2	12.320 2	12.320 2
Turbokiller lance with stainless steel pipe	41.072	41.580-05	41.072 7	41.580-11
Stainless steel lance with flat jet nozzle	12.392 2-D2504	12.392 2-D2505	12.392 2-D2507	12.392 2-M2011
Water filter	–	–	–	13.310