



		WS 800 TS		WS 1000 TS		WS 1200 TS	
Technical specifications							
Operating pressure adjustable	bar / MPa	30-250 / 3-25		30-200 / 3-20		30-180 / 3-18	
Max. admissible overpressure	bar / MPa	270 / 27		230 / 23		200 / 20	
Connected load	V / ~ / Hz / A	400 / 3 / 50 / 12		400 / 3 / 50 / 12		400 / 3 / 50 / 12	
Motor speed	Rpm	1400		1400		1400	
Water output	l/min l/h	13.3	798	16	960	19	1140
Power intake / Power output	kW kW	7.5	5.5	7.5	5.5	7.5	5.5
Power supply cable	m	7.5		7.5		7.5	
Dimensions L x W x H	mm	670 / 430 / 510		670 / 430 / 510		670 / 430 / 510	
Weight	kg	62		62		62	
Cleaning Agent Intake		-		-		-	
Equipment							
Hose drum		-		-		-	
Steel braided high-pressure hose	m	10		10		10	
Trigger gun with safety catch	Model	Starlet		Starlet		Starlet	
Stainless steel lance with flat jet nozzle	Nozzle size	● 04		● 05		● 07	
Ord.no.		4131300		4131310		4131320	


TECHNICAL HIGHLIGHTS!

AUTOMATIC HOSE REEL - SET

Automatic hose reel - Set for the ideal usage of the WS series as wall unit.

- Hose drum made of stainless steel
- Swivelling wall holder
- Connecting hose 2 m

For more on this, see page 59 (Hose drums / Retrofitting sets)



For detailed technical information, see page 80